




XtraBond™9500
Advanced Polymer Sealant

XtraBond™9500 Advanced Polymer Sealant is a low-modulus, moisture curing advanced polymer adhesive and sealant. XtraBond™9500 meets or exceeds the requirements of ASTM C920 Type S, Grade NS, Class 25, Use NT, G, A, M; Federal Specification TT-S-00230C Type II, Class A.



XtraBond™9550
Advanced Polymer Sealant

XtraBond™9550 Advanced Polymer Sealant meets or exceeds the requirements of ASTM C920 Type S, Grade NS, Class 50, Use NT, G, A, M; Federal Specification TT-S-00230C Type II, Class A.



XtraBond™9500XHS
High-Strength Advanced Polymer Sealant

XtraBond™9500XHS High-Strength Advanced Polymer Sealant meets or exceeds the requirements of ASTM C920 Type S, Grade NS, Class 25, Use NT, G, A, M; Federal Specification TT-S-00230C Type II, Class A.



XtraBond™9500NC
New Construction Advanced Polymer Sealant

XtraBond™9500NC New Construction Advanced Polymer Sealant meets or exceeds the requirements of ASTM C920 Type S, Grade NS, Class 25, Use NT, G, A, M; Federal Specification TT-S-00230C Type II, Class A.



XtraBond™9500UC
Advanced Polymer Sealant

XtraBond™9500UC Ultra-Clear Advanced Polymer Sealant meets or exceeds the requirements of ASTM C920 Type S, Grade NS, Class 12.5, Use NT, G, A, M; Federal Specification TT-S-00230C Type II, Class B.



XtraBond™9500TX
Advanced Polymer Sealant

XtraBond™9500TX Textured Advanced Polymer Sealant meets or exceeds the requirements of ASTM C920 Type S, Grade NS, Class 12.5, Use NT, G, A, M; Federal Specification TT-S-00230C Type II, Class B.



XtraBond™9500SL
Advanced Polymer Sealant

XtraBond™9500SL is a high performance, one component advanced polymer sealant that is self-leveling and permanently flexible. XtraBond™9500SL meets or exceeds the requirements of ASTM C920 Type S, Grade P, Class 25, Use NT, A, G, and M.



TerraMax®925
Eco-Friendly Flooring Products

TerraMax®925 is an all-in-one, single step, advanced polymer flooring adhesive. The high performance wood floor adhesive contains no water or solvents and very low VOCs, so it's easy on installers and the environment





XtraBond™ 150
RTV Silicone Sealant

XtraBond™150 is an extended acetoxy-based, permanently flexible, one-component sealant. This economical acetoxy sealant can withstand up to 300°F continuously and is perfect for general construction projects. This sealant is offered in a wide variety of colors using our Custom Color Matching & Mixing system.



XtraBond™ 250
100% RTV Silicone Sealant

XtraBond™250 is a 100% acetoxy-based, high performance, one-component silicone sealant. XtraBond™250 meets or exceeds the requirements of NSF/ANSI 51 - Food Equipment Materials, so it can be used confidently around all food contact types up to 400°F continuously. This product is only available in Almond, Aluminum Stone, Black, Clear, White, Bronze, and Translucent.



XtraBond™ HT
High-Temp RTV Silicone Sealant

XtraBond™HT is a 100% acetoxy-based, high temperature performance, one-component silicone sealant. XtraBond™HT meets or exceeds the requirements of NSF/ANSI 51 - Food Equipment Materials, so it can be used confidently around all food contact types up to 500°F continuously, while maintaining integrity up to 600°F. This product is only available in Red.



XtraBond™ 450
Neutral Cure Silicone Sealant

XtraBond™450 is a neutral cure, high performance, one-component silicone sealant. XtraBond™450 meets or exceeds the requirements of ASTM C920 Type S, Grade NS, Class 35, Use NT, G, M, A; Federal Specification TT-S-00230C Type II, Class A; Federal Specification TT-S-001543A Type Non-Sag, Class A; AAMA 802.3-16 Type II; AAMA 803.3-16 Type I; AAMA 808.3-16. Also available in a Clear & Black Fast Set formula.



XtraBond™ 25
Acrylic Latex Caulk

XtraBond™25 is an economical, multi-purpose acrylic latex caulk. This product meets the requirements of ASTM C834 Grade NF, Type OP and is only available in white.



XtraBond™ 50
Siliconized Acrylic Sealant

XtraBond™50 is a siliconized acrylic latex sealant. This product meets the requirements of ASTM C834 Grade NF, Type OP and is offered in a wide variety of colors using our Custom Color Matching & Mixing system. XtraBond™50 is also available in clear, which meets the requirements of ASTM C834 Grade -18°C, Type C.



XtraBond™ 100
Siliconized Acrylic Sealant

XtraBond™100 is a premium grade multi-purpose siliconized acrylic latex sealant. The product is engineered to provide excellent adhesion to vinyl, aluminum, wood, sheet metal & most common building materials without need of a primer. The addition of a silicone polymer provides greater flexibility than other latex products.





XtraBond™ 9714 Liquid Applied Flashing

XtraBond™9714 is a one-component, moisture curing liquid applied flashing and sealant. XtraBond™9714 meets or exceeds the requirements of ASTM C920 Type S, Grade NS, Class 35, Use NT, G,A, M,O. AAMA 714: Specification for Liquid Applied Flashing used to Create a Water-Resistive Seal around Exterior Wall Openings in Buildings.



XtraFlash® Membrane Water & Moisture Barrier System

XtraFlash® Membrane Flashing is an aggressive self-adhering waterproof butyl-based flashing membrane that adheres to plywood, OSB, masonry, aluminum, vinyl, steel, drywall, and house-wrap. The membrane is based on our proven water and moisture vapor barrier technology. It's perfect for use around windows & doors, joints & vents, pot shelves & recessed windows and virtually any opening that requires a high-performance waterproof barrier.



XtraFlash® Nail-On Water & Moisture Barrier System

XtraFlash® Nail-On Flashing is a heavy duty, flexible, tear resistant, woven polypropylene designed to prevent moisture and water intrusion when used around windows and doors. The cross-woven design allows it to be mechanically fastened with staples or capped nails.



XtraBond™ 1500 Premium Grade Butyl Sealant

XtraBond™1500 is a one component, gun grade, permanently flexible, general purpose butyl rubber sealant. Manufactured for excellent adhesion to glass, wood, roof tile, concrete, clay, slate, sheet metal, most common building materials and most plastics. XtraBond™1500 has excellent weatherability and stays permanently elastic even when exposed to both high and low temperatures.



XtraBond™ 1500NS Non-Skinning Premium Grade Butyl Sealant

XtraBond™1500NS is a non-skinning, solvent release butyl rubber sealant. XtraBond™1500NS will remain permanently pliable, making it an ideal choice for applications such as walk in coolers and freezers.



XtraBond™ 2500 Co-Polymer Sealant & Adhesive

XtraBond™2500 Co-Polymer is a permanently flexible, high performance solvent-release adhesive/sealant. Manufactured for excellent adhesion and performance to a wide variety of roofing substrates, tile, concrete, clay, slate, pre-painted metals, masonry, stone, aluminum, and sheet metal without the need of a primer.



General Properties of Various Sealants

	Advanced Polymer	Acetoxy Silicone	Neutral Silicone	Latex	Butyl
Paintable	✓	X	X	✓	✓
Custom Colors	✓	✓	✓	✓	X
Moisture Cure	✓	✓	✓	X	X
Weather Resistance	Good	Excellent	Excellent	Poor	Good
Movement	Up to ± 50%	Up to ± 25%	Up to ± 35%	X	X
VOC Compliant	✓	✓	✓	✓	✓
Odor	Mild	Heavy	Moderate	Mild	Moderate



Premier Building Solutions develops and manufactures high performance materials and systems that provide protection in commercial and residential buildings, as well as a variety of other industrial and transportation applications. These products have set the standard in the industry for quality and performance. The company's history of innovation has led to the development of breakthrough adhesive chemistries and new industrial-strength products that help customers increase the efficiency and durability of their critical assets.



Headquarters

480 Nova Drive SE, Massillon, OH 44646

TOLLFREE: (866) 512-4583

PHONE: (330) 244-2907 | FAX: (330) 244-9423

Premier Building Solutions specifically disclaims and makes no warranties, express or implied, about this product, its merchantability, or its fitness for a particular purpose. All recommendations, directions, and suggestions for its use are consistent with our testing and research for a variety of applications, but no promises, guarantees, or warranties are being made with regard to its use, whether or not consistent with the directions, or its effectiveness for any given application. Users of this product should do so in compliance with all applicable laws and regulations. User of this product should conduct its own field test, to assure results.